



DT175MX

- O Race developed 7-port torque induction engine
- O High top speed with low down pulling power
- O Motocross style monoshock frame
- O Adjustable gas/oil shock absorber
- Long travel forks
- Cross-over expansion chamber exhaust system
- O High ground clearance duplex frame
- O Crankcase shield
- Chain guide
- O Black contoured levers
- Matt black engine for efficient heat dissipation

- Lightweight half-width hubs ribbed for strength
- O High clearance plastic guards
- O Rubber mounted indicators
- O Braced, padded handlebars
- O Engine kill button
- O Prop stand
- 6-speed gearbox
- O Electronic ignition
- Competition screw on filter cap
- O Autolube lubrication
- Trail tyres

ENGINE

Type
Cylinder
Displacement
Bore & Stroke
Compression Ratio
Maximum Horsepower
Maximum Torque
Lubrication System
Starting
Ignition Type
Transmission

2 stroke Single 171cc 66×50mm 6.8:1 16.3hp 7000rpm 1.7kg-m 6000rpm Yamaha Autolube Primary kick CDI 6 speed

DIMENSIONS

Overall Length
Overall Width
Overall Height
Wheelbase
Ground Clearance
Seat Height
Weight
Fuel Tank Capacity
Oil Capacity
Tyres – Front
Rear
Brakes – Front

Rear

885mm 1120mm 1350mm 265mm 855mm 99kg 7 litres 0.9 litres 2.75–21–4PR 3.50–18–4PR Drum

2080mm