

F E A N D F C M O D E L S



1

9

HUSABERG
MOTOR AB SWEDEN

9

3

F O U R S T R O K E E N D U R O



350 & 501 NEWS: New design, better front break caliper, bigger front breakdisc, better silencer for lower noicelevel (350), stronger piston, stronger fastenpoints on the radiator, stronger connecting-rod, better system for ventilation of the engine, stronger shiftforks, stronger gearwheels, improved character of the engine (501).

F O U R S T R O K E M O T O C R O S S



499 & 600 NEWS: New design, better break caliper, bigger front break disc, stronger fastenpoints on the radiator, stronger connecting-rod, better system for ventilation of the engine, stronger shiftforks, stronger gearwheels, improved character of the engine.

TECHNICAL SPECIFICATION

Technical specification	350 cc	499 cc	501 cc	600 cc
Model:	Husaberg FE 350	Husaberg FC 499	Husaberg FE 501	Husaberg FC 600
Engine:	Watercooled 4 valves, single four stroke	Watercooled 4 valves, single four stroke	Watercooled 4 valves, single four stroke	Watercooled 4 valves, single four stroke
Bore/Stroke:	86 x 60,2	92 x 75	92 x 75,5	95 x 84
Displacement:	349 cc	499 cc	502 cc	595 cc
Compression:	10,8 : 1	11,0 : 1	10,2 : 1	10,5 : 1
Carburator:	Dellorto ø 38	Dellorto ø 38	Dellorto ø 38	Dellorto ø 38
Transmission:	6 gears	4 gears	6 gears	4 gears
Ignition:	SEM electronic, 140 Watt	SEM electronic, 140 Watt	SEM electronic, 140 Watt	SEM electronic, 140 Watt
Wheelbase:	1490 mm	1490 mm	1490 mm	1490 mm
Length:	2160 mm	2160 mm	2160 mm	2160 mm
Tire, front:	3.00" x 21"	3.00" x 21"	3.00" x 21"	3.00" x 21"
Tire, rear:	4,50" x 18"	4,50" x 18"	4,50" x 18"	4,50" x 18"
Front suspension:	WP "Upside-down" 295 mm	WP "Upside-down" 295 mm	WP "Upside-down" 295 mm	WP "Upside-down" 295 mm
Rear suspension:	Öhlins 328 mm	Öhlins 328 mm	Öhlins 328 mm	Öhlins 328 mm
Hydraulic brakes, front:	Disc ø 260 mm	Disc ø 260 mm	Disc ø 260 mm	Disc ø 260 mm
Hydraulic brakes, rear:	Disc ø 220 mm	Disc ø 220 mm	Disc ø 220 mm	Disc ø 220 mm
Tank capacity:	8,5 liter	8,5 liter	8,5 liter	8,5 liter
Seat height:	950 mm	950 mm	950 mm	950 mm
Ground clearance:	390 mm	390 mm	390 mm	390 mm
Frame hardened:	CrMo-steel	CrMo-steel	CrMo-steel	CrMo-steel
Weight:	108 kg	106 kg	109 kg	107 kg



SKF

Sponsor Team Husaberg 1993

Utvecklingsfonden
ÖREBRO LÄN

HUSABERG
MOTOR AB SWEDEN