

YAMAHA RD50MX-More power more style

Big bike feel, big bike style and big bike performance, that's what we set out to achieve with the RD50. The all new engine was developed to provide sharp, snappy acceleration and tireless cruising using Yamaha's patented Torque Induction system to aid economy and clean running. The deep finned barrel and piston ensures the high performance engine maintains an efficient working temperature whilst Autolube lubrication provides a constant supply of clean oil at all engine speeds. The advanced chassis technology developed from Kenny Roberts' racing programme was employed to produce the fine taut handling demanded by todays discerning young motorcyclist. Monoshock rear suspension controlled by a single de-carbon type damper and long travel front forks. Throughout the project stylists worked alongside the engineers to produce the exciting lines. Sleek, smooth tank, racy matt black expansion exhaust and neat practical headlamp cowl proclaim the RD50 as the finest sports lightweight available.







ENGINE

Yamaha is the biggest producer of two stroke engines in the world, with 25 years of development by Yamaha on the race track and road. Featuring a reed valve inlet the engine on the RD50MX is torquey and responsive in all conditions.



Suspension on the RD50MX is Yamaha's Monoshock system, just like on our factory racers, featuring a single shock absorber and a strong triangulated swinging arm which gives the bike excellent handling and increases rider comfort.






OILPUMP

Another feature on the RD50MX is the Yamaha Autolube lubrication system. A small pump ensures exactly the right amount of lubricant is fed to the engine from the oil tank, increasing engine life and reliability.

INSTRUMENTS

A stylish instrument console features a speedometer, rev. counter and mileage recorder as well as neutral, oil and indicator warning lights protected by a sleek cowling.





SPECIFICATION

ENGINE

Type 2 stroke, reed valve Cylinder Single

Displacement 49cc

Bore and stroke 40 x 39.7mm

Compression ratio 6.6:1

Max. horsepower
Max. torque
Lubrication
Starting
Ignition

2.9hp 5500rpm
0.40kg-m 4000rpm
Yamaha Autolube
Primary kick
Flywheel magneto

Transmission 5-speed

CHASSIS

Overall length 1935mm Overall width 745mm Overall height 1065mm Wheelbase 1240mm Ground clearance 170mm Seat height 790mm 82kg 13.0 litres Weight Fuel tank capacity Oil capacity 1.3 litres

Tyres

Front 2.50–18–4PR Rear 2.75–18–4PR

Brakes

Front Disc Rear Drum

