

VL125

 **SUZUKI**



The Real Look and Real Ride on a 125cm³ Cruiser

Offering the real look and real ride of an authentic American cruiser like its 1500cm³ brother, the Intruder LC125 changes all the rules of the 125cm³ class. Large seat, long wheelbase, kicked-out front end and pullback bars. Fat tires, massive tank. Quality details. Thumping 65-degree V-Twin with sophisticated ignition-timing control and advanced gear shift technology. All the right stuff to turn heads while you cruise in comfort.

VL125




YD8 : Metallic Sonic Silver


- The 124 cm³, 3-valves-per-cylinder, 65-degree-V engine brings you a thumping V-Twin power delivery and smooth operation.
- Cutting-edge engine features include a throttle position sensor that adjusts the ignition timing of the independent front and rear cylinder three-dimensional ignition maps to match the engine rpm for optimized combustion efficiency, and Suzuki's own Black Fluoro-coated pistons.
- Cruise in comfort with the Intruder LC125's long wheelbase, kicked-out front end, large and low seat, pullback handlebars, and beefy 18-inch front and 15-inch rear tires. The pillion seat can be removed to fully expose the rear fender.
- Large 5-liter underseat storage compartment. Wire-lock for a

helmet included.

- Gleaming chrome-plated components include the sweeping dual mufflers, air cleaner cover, spoked wheels, and the tank mounted speedometer.
- Lustrous paint graces the voluminous fuel tank and the deep, flared fenders.
- High-quality instruments, including an electrically controlled speedometer and an LCD odometer/tripmeter.



124 cm³ V-Twin engine



5-liter storage compartment



High-quality instruments

VL125 SPECIFICATIONS

Engine type	4-stroke, 2-cylinder, 65° V-Twin, air-cooled, SOHC	
Piston displacement	124 cm ³	
Bore × stroke	44.0 mm × 40.9 mm	
Compression ratio	10.3 : 1	
Carburetor	MIKUNI BDS26SS	
Starter system	Electric	
Transmission	5-speed constant mesh	
Drive system	Chain, 142 links	
Overall length	2,240 mm (88.2 in.)	
Overall width	880 mm (34.6 in.)	
Overall height	1,110 mm (43.7 in.)	
Wheelbase	1,520 mm (59.8 in.)	
Ground clearance	150 mm (5.9 in.)	
Seat height	685 mm (27.0 in.)	
Dry mass	140 kg (308 lbs)	
Suspension	front	Telescopic, coil spring, oil damped
	rear	Swingarm, coil spring, oil damped, spring preload 5-way adjustable
Brakes	front	Disc
	rear	Drum
Tires	front	90/90-18 51P or 90/90-18 M/C 51P
	rear	130/90-15 M/C 66P
Ignition type	Electronic ignition	
Fuel tank	12.0 L (3.2 US gal.)	
Body colors	Y7H : Pearl Dark Space Blue YD8 : Metallic Sonic Silver	

Specifications shown have been achieved by production models under standard operating conditions. Data is intended to describe the motorcycle fairly but may not apply to every machine. Suzuki reserves the right to change specifications, equipment, materials, colour or any other item without notice. Actual colours may differ from the colours printed in this brochure. Please confirm the full specification of a particular machine with your dealer prior to purchase. All details correct at time of going to print.

- Always wear approved helmet, eye protection and protective clothing
- Read and understand the owner's manual before riding the machine
- Never ride under the influence of alcohol or other drugs

For more information, contact your local Authorised Suzuki Dealer or telephone the 24 hour hotline: 01892 707001 www.suzuki.co.uk Suzuki Information Department, P.O. Box 56, Tunbridge Wells, Kent TN11 2XY

Date of Preparation - March 2002

Part No: MB02VL125-LEAF

 **SUZUKI**
Ride the winds of change