



ENDUCROSS EC-06

250

300

GASGAS

New features **250 | 300**



ENDUCROSS EC-06 250 300

ENGINE

DISPLACEMENT	249.3 cm ³ / 297 cm ³
TYPE	Two-stroke single cylinder, with reed valves directly
	to crankcase and exhaust valve
COOLING SYSTEM	
DIAMETER FOR STROKE	66.4 x 72 mm / 72 x 72 mm
CARBURETTOR	Keihin* PWK
CLUTCH	
GEARBOX	
IGNITION	Digital magnetic flywheel, CDI Kokusan*
TRANSMISSION	Primary with gears, secondary with chain
MOTOR LUBRICATION	2% mixture
GEARBOX AND CLUTCH LUBRICATION	900 cm ³ oil type API SF or SG 10W30 (EC 250)

CHASSIS

CHASSIS	Deltabox made of rectangular cromoly tubes
FRONT SUSPENSION	Inverted Marzocchi* forks, diam. 45 mm, displacement
	295 mm. Inverted Öhlins* forks, displacement 295 mm
REAR SUSPENSION	Aluminium swing arm Öhlins. Progressive single
	shock absorber system, displacement 310 mm
FRONT BRAKES	260 mm Disk Nissin Pump and
	Nissin* piston calliper
REAR BRAKES	220 mm Disk Nissin Pump and
	Nissin* piston calliper
WHEEL RIMS	D.I.D.* Wheel rims
FRONT TYRE	90 x 90 - 21"
REAR TYRE	140 x 80 - 18"
ACCELERATOR	Domino*
STARTER PEDAL	
GEAR AND BRAKE PEDALS	Forged aluminium with retractable tip

DIMENSIONS

DISTANCE BETWEEN AXLES	1,476 mm
HEIGHT OF SEAT	
FUEL TANK CAPACITY	
UNLOADED WEIGHT	102 kg (EC 250), 103 kg (EC 300)





















