



ENGINE Displacement

Bore and Stroke Compression ratio Maximum torque

Carburetion Ignition Starting Lubrication

-stroke, single 47 x 42 mm 4.0 ft -lbs

(I) TK V16P-3 Autolube

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Oil tank capacity Suspension Front

Brakes

Front

Fron

1.3 gals. (4.8 i Telescopic forks

27.2" (690 mm) 36.6" (930 mm) 41.1" (1,045 mm)

7.7" (195 mm

130 lbs. (59 kg)

Drum

2.50 x 15

ENGINE

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 40.0 x 39.7 mm

6.6 : 1 2.5 ft.-lbs. • (1) Mikuni VM10SC

Magneto

Autolube

2-range automatic

Tires

CHASSIS Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel rank capacity

Oil tank capacity Suspension Brakes

61.6" (1,565 mm) 26.2" (665 mm) 36.4" (925 mm)

> 0.9 gals. (3.5 i) 1.48 qts. (1.4 i) Telescopic forks

4 00 x 8 Competition Yellow



ENGINE Displacement Bore and Stroke

Compression ratio Maximum torque Carburetion Ignition Starting Lubrication

2-stroke single 47 x 42 mm 7.1 : 1 4.3 ft.-lbs. (I) TK Y16P-3A Autolube

CHASSIS Overall length Overall width Wheelbase Ground clearance Dry weight

Fuel tank capacity Oil tank capacity Suspension Front Brakes Front

Tires

Front

28.0" (710 mm) 36.6" (930 mm) 41.1" (1,045 mm) 1.3 gals, (4.8 i)

Telescopic forks

2.50 x 15

IF YOU CAN'T FIND THE MOT



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission

Street

2-stroke, single

49 cc 40 x 39.2 mm 60 . 1 2.7 ft.-lbs. (0.37 kg-m)@3,500 rpm (1) Mikuni VM12SC

Kick

C.D.I. Rear Autolube Automatic/shaft Rear

Overall length Overall width Overall height Wheelbase Ground clearance

> Oil capacity Suspension Front

Brakes Front Tires

Front Rear Coloring

CHASSIS

61.0" (1,550 mm) 26.0" (670 mm) 38.0" (965 mm) 41.3" (1,050 mm) 4.7" (110 mm) 951 lbs. (43 kg) Dry weight 0.5 gals. (2.3 f) Fuel tank capacity 0.8 qts. (0.8 f)

Telescopic forks Swing arm

Drum Drum

2.00 x 14 2.25 x 14 Majolica Blue Sunshine Red





ENGINE

Type Displacement Bore and stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission

2-stroke,

64 x 62 mm

29.7 ft.-lbs.

(4.1kg-m)

@6,000 rpm

(2) Mikuni

VM 28SC

Autolube

6-speed

Battery

Kick

twin

398 cc

6.4:1

CHASSIS Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Oil capacity

Suspension Front Rear Brakes

Front Rear Tires

Coloring

Swing arm Front 3.25S x 18 Rear

78.9" (2,005 mm) 32.7" (830 mm) 42.9" (1,090 mm) 52.0" (1,320 mm) 6.1" (155 mm) 342 lbs. (155 kg) 4.4 gals. (16.5 f) 1.7 qts. (1.6 l)

Telescopic forks

Hydraulic disc (1) Hydraulic disc (1)

3.50S x 18 New Pearl White



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission

ENGINE

Displacement

Carburetion

Lubrication

Transmission

Ignition

Starting

Bore and Stroke

Compression ratio

Maximum torque

Type

4-stroke, S.O.H.C. twin 391 cc 69 x 52.4 mm

9.3:1 23.2 ft.-lbs. (3.2kg-m)@8,000 rpm (2) Mikuni

BS 34 Battery Kick & Electric Wet sumr 6-speed

4-stroke,

391 cc

93.1

23.2 ft.-lbs.

@8,000 rpm

(3.2kg-m)

(2) Mikuni

Wet sump

BS34

Kick

Battery

6-speed

S.O.H.C. twin

69.0 x 52.4 mm

CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Oil capacity Suspension

Front Rear Brakes Front

Rear Tires Front Rear

Coloring

Overall length

Overall width

Overall height

Ground clearance

Fuel tank capacity

Wheelbase

Dry weight

Oil capacity

Suspension

Front

Rear

Brakes

Rear

Front

Rear

Coloring

Tires

Front

34.1" (865 mm) 44.9" (1,140 mm) 53.7" (1,365 mm)

5.9" (150 mm) 370 lbs. (168 kg) 3.7 gals. (14 f) 2.7 qts. (2.6 f)

81.3" (2,065 mm)

Telescopic forks Swing arm

Hydraulic disc (1) Hydraulic disc (1)

3.00S x 18 3.50S x 18 Star Blue Metalic Magnum Maroon

81.3" (2,065 mm)

33.3" (845 mm) 44.5" (1,130 mm)

53.7" (1,365 mm)

5.9" (150 mm)

351 lbs. (159 kg)

3.7 gals. (14 f)

2.7 qts. (2.6 f)

Telescopic forks

Swing arm

3.00S x 18

3.50S x 18

Black Gold

Drum

Drum



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

28.

Dr

Carburetion

Ignition Starting Lubrication Transmission



ENGINE

Displacement Bore and Stroke Compression ratio

Carburetion Ignition Starting

Type Maximum torque

Lubrication

Transmission

DRCYCLE YOU WANT IN HERE, YOU DON'T WAN'I



Overall width 4 mm

-lbs (-m) 00 rpm

455

Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Oil capacity Suspension Front Rear Brakes Front Rear Tires Front Rear

Coloring

82.9" (2,105 mm) 32.9" (835 mm) 45.3" (1,150 mm) 55.5" (1,410 mm) 6.5" (165 mm) 359 lbs. (163 kg) 3.2 gals. (12.0 f) 2.3 qts. (2.2 f)

Telescopic forks Swing arm

Hydraulic disc (1) Hydraulic disc (1)

3.50S x 19 4.00S x 18 Black Gold Chappy Red



Overall length roke. .H.C. twin Overall width Overall height 74 mm Wheelhase Ground clearance 8 ft.-lbs Dry weight kg-m) Fuel tank capacity ,000 rpm Oil capacity Mikuni Suspension **BS38**

Front

Rear

Brakes

Front

Rear

Front

Rear

Coloring

Tires

ctric & Kick

2.64 qts. (4 l) Telescopic forks Swing arm

Hydraulic disc (1)

85.8" (2.180 mm)

35.4" (900 mm)

45.7" (1,160 mm)

56.5" (1,435 mm)

5.5" (140 mm)

463 lbs. (210 kg)

4.0 gals. (15 f)

3.50H x 19 4.00H x 18 Cobalt Blue



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission

ENGINE

Displacement

Carburetion

Ignition

Starting

Lubrication

Transmission

Bore and Stroke

Compression ratio

Maximum torque

Type

4-stroke, S.O.H.C. twin 653 cc

75 x 74 mm 8.5:1 39.8 ft -lbs (5.5kg-m) @5,500 rpm (2) Mikuni

4-srtoke.

653 cc

8.5:1

S.O.H.C. twin

75 x 74 mm

39.8 ft.-lbs.

(5.5kg-m)

@5,500 rpm

Electric & Kick

(2) Mikuni

Wet sump

5-speed

BS 38

Battery

BS38 Battery Kick & Electric Wet sump 5-speed

> Front Rear Coloring

> > CHASSIS

Overall length

Overall width

Overall height

Ground clearance

Fuel tank capacity

Wheelbase

Dry weight

Oil canacity

Suspension

Front

Rear

Brakes

Front

Rear

Front

Rear

Coloring

Tires

CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Oil capacity Suspension Front Rear

Brakes Front Rear Tires

ENGINE

Type

83.5" (2,120 mm)

36.4" (925 mm)

48.0" (1,220 mm)

56.5" (1,435 mm)

5.3" (135 mm)

452 lbs. (205 kg)

3.0 gals. (11.5 f)

2.6 qts. (2.5 f)

Telescopic forks

Hydraulic disc (1)

New Yamaha Black

83.5" (2,120 mm)

36.4" (925 mm)

48.0" (1,220 mm)

56.5" (1,435 mm)

5.3" (135 mm)

463 lbs. (210 kg)

3.0 gals. (11.5 f)

Telescopic forks

Hydraulic disc (1)

Hydraulic disc (1)

Swing arm

3.50S x 19

130/90S x 16

Carmine Red

Black Gold

2.6 qts. (2.5 f)

Swing arm

3.50S x 19

130/90S x 16

Drum

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition

Starting Lubrication Transmission CHASSIS

BS34-II

Transistor

controlled

Wet sump

5-speed/shaft

4-stroke, Overall length D.O.H.C. triple Overall width 747 cc Overall height 68 x 68.6 mm Wheelhase 9.2:1 Ground clearance 47 ft.-lbs Dry weight (6.5kg-m) Fuel tank capacity @6,500 rpm Oil capacity (3) Mikuni Suspension

Front Rear Brakes Front

Kick & Electric Tires Front

3.25H x 19 4.00H x 18 Rear Coloring Vintage Burgundy Black Gold

ENGINE Type

Displacement Bore and stroke Compression ratio Maximum torque

Ignition

Starting Lubrication Transmission

CHASSIS Overall length Overall width Overall height

Carburetion

4-stroke, D.O.H.C. four 1,101 cc 71.5 x 68.6 mm Wheelbase 9.2:1 Ground clearance 66.6 ft.-lbs. Dry weight (9.2kg-m) Fuel tank capacity @6.500 rpm Oil capacity

(4) Mikuni

Transistor

controlled

Wet sump


5-speed/shaft

BS34-II

Suspension Front Rear Brakes Front Kick & Electric

Rear Tires Front

Rear Coloring



84.3" (2,140 mm)

35.4" (900 mm)

46.3" (1,175 mm)

57.1" (1,450 mm)

5.5" (140 mm)

522 lbs. (237 kg)

4.5 gals. (17 f)

3.7 qts. (3.5 l)

Telescopic forks

Hydraulic disc (2)

Hydraulic disc (1)

Swing arm

Displacement Bore and Stroke Compression ratio Maximum torque

Starting Lubrication

4-stroke. D.O.H.C. four 1,101 cc 71.5 x 68.6 mm 9.2:1 66.6 ft.-lbs. (9.2kg-m)

@6,500 rpm Flectric & Kick

Overall length Overall width Overall height Wheelbase Dry weight Oil capacity Suspension Front Rear Brakes

CHASSIS

Ground clearance Fuel tank capacity

XS Eleven-SF

Front Rear Tires

Front Rear

Carburetion

Transmission

4-stroke. Overall length 85.6" (2,175 mm) Overall width 33.7" (855 mm) D.O.H.C. triple Overall height 44.8" (1,185 mm) 747 cc

Wheelbase

Ground clearance 6.1" (155 mm) 507 lbs. (230 kg) Dry weight Fuel tank capacity 4.5 gals. (17 f) Oil capacity 3.9 ats. (4 f)

> Telescopic forks Swing arm

59.3" (1.505 mm)

Hydraulic discs (2) Hydraulic disc (1)

3.25H x 19 4.00H x 18 Carmine Red, Indigo

ENGINE Type

> Displacement Bore and Stroke Compression ratio Maximum torque

Ignition

Starting Lubrication Transmission

68 x 68.6 mm 9.2:1 47 ft.-lbs (6.5kg-m) @6,500 rpm (3) Mikuni BS 34-II Transistor

controlled Kick & Electric Wet sump 5-speed/shaft

Rear

Suspension

Front Rear Brakes Rear

Front Tires Front

Coloring

Blue, Black Gold

ENGINE Type

Ignition

(4) Mikuni BS 34-II Transistor controlled Wet sumr 5-speed/shaft

Coloring

A MOTORCYCLE.



89.0" (2,260 mm) 36.2" (920 mm) 46.3" (1,175 mm) 60.8" (1,545 mm) 5.9" (150 mm) 562 lbs. (255 kg) 5.3 gals. (20 f) 4.2 qts. (4 f)

Carburetion Telescopic forks

Hydraulic discs (2) Hydraulic disc (1)

3.50H x 19 4.50H x 17 Indigo Blue Magenta Red

Swing arm



89.6" (2,275 mm) 33.7" (855 mm) 48.4" (1,230 mm) 60.8" (1,545 mm) 6.1" (155 mm) 556 lbs. (252 kg) 4.0 gals. (15 ℓ) 4.2 qts. (4 f)

Telescopic forks Swing arm

Hydraulic discs (2) Hydraulic disc (1)

3.50H x 19 130/90H x 16 Black Gold Carmine Red



2-stroke, single 97 cc 52 x 45.6 mm 6.7:1 6.3 ft.-lbs.

(0.87kg-m) @6,500 rpm (1) Mikuni VM22SS Magneto Kick

Autolube 5-speed

CHASSIS Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Oil capacity

Front Rear Brakes Front

Suspension

Rear Tires Front Rear Coloring

2.50 x 18 3.00 x 16 Clean White Leaves Green



176.4 lbs. (80 kg) 1.19 gals. (4.5 f) 1.06 qts. (1.0 f) Telescopic forks

7.9" (200 mm)

Swing arm

Drum

Drum

Carburetion Ignition Starting Lubrication Transmission

ENGINE

Displacement

Bore and Stroke

Compression ratio

Maximum torque

Type

2-stroke single 171 cc 66 x 50 mm 6.8:1 12.0 ft.-lbs (1.66kg-m) @6,500 rpm (1) Mikuni VM24SS

C.D.I. Kick Autolube 6-speed

CHASSIS Overall length Overall width Overall height Wheelhase Ground clearance Dry weight Fuel tank capacity Oil capacity Suspension

Front Rear Brakes Front Rear

Tires Front Rear Coloring 82.5" (2,095 mm) 33.5" (850 mm) 44.9" (1,140 mm) 53.1" (1,350 mm) 10.4" (265 mm) 216 lbs. (98 kg) 1.8 gals. (6.8 f) 1.76 qts. (1.0 f)

Telescopic forks Monocross suspension

Drum Frum

2.75 x 21 3.50 x 18 Crystal Silver Sunshine Red



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission Overall length

4-stroke,

S.O.H.C.

single

499 cc

9.0:1

@5,500 rpm

(1) Mikuni

VM32SS

Magneto

Dry sump

5-speed

Kick

Overall width Overall height Wheelbase 87 x 84 mm Ground clearance Dry weight 28.2 ft.-lbs. Fuel tank capacity (3.9kg-m) Oil capacity

Suspension Front Rear Brakes Front Rear

Tires Front Rear Coloring

84.8" (2,155 mm) 34.4" (875 mm) 46.5" (1,180 mm) 55.9" (1,420 mm) 8.9" (225 mm) 304 lbs. (138 kg) 2.2 gals. (8.5 f)

2.3 qts. (2.2 f) Telescopic forks

Swing arm Drum

3.00 x 21 4.00 x 18 Clean White

Drum



ENGINE Type

ENGINE

Displacement

Bore and Stroke

Compression ratio

Maximum torque

Type

Ignition

Starting

Lubrication

Transmission

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission CHASSIS

2-stoke,

single

123 cc

7.2:1

56 x 50 mm

9.8 ft.-lbs.

(1.35kg-m)

(1) Mikuni

VM24SS

Magneto

Autolube

6-speed

Kick

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity @6,500 rpm Oil tank capacity Suspension

Front Rear Brakes Front Rear Tires Front Rear

Coloring

82.5" (2,095 mm) 33.5" (850 mm) 44.9" (1.140 mm) 53.1" (1,350 mm) 10.4" (265 mm) 214 lbs. (97 kg) 1.8 gals. (6.8 f)

> 1.76 qts. (1.0 f) Telescopic forks Monocross suspension

Drum Drum

2.75 x 21 3.50 x 18 Diamond Blue Competition Yellow ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission

2-storke, single 246 cc 70 x 64 mm 6.7:1 20.3 ft.-lbs.

(2.8kg-m) @5,000 rpm (1) Mikuni VM28SS C.D.I. Kick Autolube 5-speed

CHASSIS

DT250

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Oil capacity Suspension

Front Rear Brakes Front Rear

Tires Fron Rear Coloring 86.0" (2,185 mm) 34.3" (870 mm) 45.9" (1.165 mm) 55.9" (1,420 mm) 10.2" (260 mm) 270.5 lbs. (122.7 kg) 2.2 gals. (8.5 f) 1.2 qts. (1.1 f)

Telescopic forks Monocross suspension

Drum Drum

3.00 x 21 4.00 x 18 Competition Yellow



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 4-stroke, S.O.H.C. single 499 cc 87 x 84 mm 9.0:1 28.9 ft.-lbs. (4.0kg-m) @5,500 rpm

(1) Mikuni VM34SS Magneto Kick Dry sump 5-speed

CHASSIS

Brakes

Front

Rear

Front

Rear

Coloring

Tires

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity 2.2 gals. (8.5 f) Oil capacity Suspension Front Rear

Telescopic forks Swing arm

> Drum Drum

> > 3.00 x 21 4.60 x 18

New El Toro Orange

83.3" (2,115 mm)

34.4" (875 mm)

45.5" (1.155 mm) 55.9" (1,420 mm)

9.1" (230 mm)

271 lbs. (123 kg)

2.3 qts. (2.2 l)

YAMAHA: WHEN YOU KN



ENGINE Type Displacement

Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 52 x 45.6 mm

2-stroke

97 cc

6.7:1

6.3 ft.-lbs.

(0.87kg-m)

(1) Mikuni

VM22SS

Magneto

Autolube

2-stroke,

66 x 50 mm

12.7 ft.-lbs.

(1.76kg-m)

(1) Mikuni

VM24SS

Autolube

6-speed

C.D.I.

Kick

@6,000 rpm

single

171 cc

6.8:1

5-speed

Kick

@6,500 rpm

Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity

Overall length

Oil capacity Suspension Front Rear

Brakes Front Rear

Tires Front Rear Coloring

70.7" (1,795 mm) 31.5" (800 mm) 37.8" (960 mm) 46.9" (1,190 mm) 7.9" (200 mm) 170 lbs. (77 kg) 1.19 gals. (4.5 f) 1.06 qts. (1.0 t)

Telescopic forks Swing arm

Drum Drum

2.50 x 18 3.00 x 16 Clean White



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity

Oil tank capacity Suspension Front Rear Brakes

Front Rear Tires Front

Rear

Coloring

82.1" (2,085 mm) 34.1" (865 mm) 43.5" (1,105 mm) 52.8" (1,340 mm) 9.8" (250 mm) 201 lbs. (91 kg) 1.8 gals. (6.8 f) 1.06 qts. (1.0 f)

> Telescopic forks Monocross suspension

Drum Drum

2 75 x 21 3.50 x 18 Clean White



ENGINE Type Displacement

Bore and Stroke Compression ratio Maximum torque

Ignition Starting Lubrication Transmission

Carburetion

2-stroke, single 49 x 42 mm 7.0:1 6.9 ft.-lbs.

(0.96kg-m)@9,500 rpm (1) Mikuni VM26SS C.D.I. Kick

Front Wheel travel Rear Pre-mix (20:1) Wheel travel 6-speed

Brakes Front Rear Tires Front Rear

Suspension

CHASSIS Overall length

67.5" (1,715 mm) Overall width 30.9" (785 mm) Overall height 38.0" (965 mm) Wheelbase 46.4" (1,180 mm) Ground clearance 7.9" (200 mm) 143 lbs. (65 kg) Dry weight Fuel tank capacity 1.2 gals. (4.6 f)

> Telescopic forks 165 mm Monocross suspension 145 mm

> > Drum Drum

2.50 x 16 3.60 x 14



ENGINE

Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 2-stroke

single 98 cc 50 x 50 mm 7.2:1 9.8 ft.-lbs (1.36kg-m)

@10,000 rpm (3) Mikuni VM30SS C.D.I. Kick Pre-mix (20:1)

6-speed

CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Suspension

Front Wheel travel Rear Wheel travel Brakes

Front Rear Tires Front Rear

Coloring

80.3" (2,040 mm) 35.0" (890 mm) 44.3" (1,125 mm) 53.7" (1,365 mm) 11.0" (280 mm) 183 lbs. (83 kg)

1.3 gals. (5.0 ℓ)

Telescopic forks 180mm Monocross suspension 172 mm

Drum Drum

3.00 x 21 3.50 x 18 Competition Yellow



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 2-stroke single 123 cc 56 x 50 mm 8.3:1 12.4 ft.-lbs (1.7kg-m) @10,500 rpm

(1) Mikuni VM32SS C.D.I. Kick Pre-mix (20:1) 6-speed

Overall length Overall width Overall height Wheelbase

Ground clearance Dry weight Fuel tank capacity Suspension Front

Wheel travel Rear Wheel travel Brakes

Rear

Tire

Front Front 1.6 gals. (6.1 f) Telescopic forks 250 mm Monocross suspension 240 mm

82.5" (2,095 mm)

37.4" (950 mm)

45.9" (1,165 mm)

55.5" (1,410 mm)

11.4" (290 mm)

194 lbs. (88 kg)

Drum Drum

3.00 x 21 4.10 x 18



ENGINE

Type Displacement

Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 2-stroke, single 246 cc 70 x 64 mm 7.9:1 25.7 ft.-lbs (3.55kg-m) @6,500 rpm

(1) Mikuni VM38SS C. D. I. Kick Pre-mix (20:1) 6-speed

CHASSIS Overall length

84.4" (2,145 mm) Overall width 36.8" (935 mm) Overall height 47.2" (1,200 mm) Wheelbase 57.1" (1,450 mm) 12.6" (320 mm) Ground clearance 218 lbs. (99 kg) Dry weight Fuel tank capacity 2.0 gals. (7.6 f) Suspension Telescopic forks

Front Wheel travel Rear Wheel travel

Brakes Front Rear

Tires

Front

Rear

Coloring

265 mm Drum Drum

270 mm

3.00 x 21 4.50 x 18

Monocross suspension

Competition Yellow

IOW HOW THEY'RE BUILT.



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 2-stroke single 396 cc 82 x 75 mm 7.3:1 32.8 ft.-lbs. (4.5kg-m)

@6,500 rpm (1) Mikuni VM38SS C.D.I. Kick Pre-mix (20:1)

5-speed

2-stroke, single

D.O.H.C.

66 x 50 mm

15.2 ft.-lbs

@7,500 rpm

Pre-mix (20:1)

(2.1kg-m)

(1) Mikuni

VM34SS

C.D.I

6-speed

Kick

171 cc

7.4:1

Brakes Front Rear Tires Front Rear

Rear

Colorin

CHASSIS Overall length

Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Suspension Front

Telescopic forks Wheel travel 270 mm Monocross suspension Wheel travel 265 mm

> Drum Drum

3.00 x 21 5.10 x 18 Competition Yellow

84.4" (2,145 mm)

36.8" (935 mm)

47.2" (1,200 mm)

57.1" (1,450 mm)

12.6" (320 mm)

225 lbs. (102 kg)

2.0 gals. (7.6 f)



ENGINE Type

Displacement Bore and stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity

Suspension Front Rear Brakes Front Rear

Tires Front Rear Coloring 84.1" (2,135 mm) 36.8" (935 mm) 44.7" (1,135 mm) 54.1" (1,375 mm) 10.2" (260 mm) 216 lbs. (98 kg)

2.5 gals. (9.5 f)

Telescopic forks Monocross suepension

Drum Drum

3.00 x 21 4.10 x 18 Sky Blue



ENGINE

Type Displacement Bore and stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission 2-stroke. single 246 cc

70 x 64 mm 79.1 24.3 ft.-lbs. (3.35kg-m) @7,000 rpm (1) Mikuni VM36SS

2-stroke,

82 x 75 mm

VM38SS

Pre-mix (20:1)

C.D.I.

5-speed

Kick

single

396 cc

C.D.I. Kick Pre-mix (20:1) 6-speed

CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Suspension

Front Rear Brakes Front Rear Tires

Front Rear Coloring

87.0" (2,210 mm) 36.8" (935 mm) 46.1" (1,170 mm) 55.9" (1,420 mm) 10.8" (275 mm) 243 lbs. (110 kg) 3.2 gals. (12 l)

Telescopic forks Monocross suspension

Drum Drum

3.00 x 21 4.50 x 18 Sky Blue



ENGINE Type

Displacement Bore and Stroke Compression ratio Maximum torque

7.3:1 31.8 ft.-lbs. (4.4kg-m) @6,500 rpm Carburetion (1) Mikuni

Ignition Starting Lubrication Transmission CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Suspension

Front Rear Brakes Front Rear Tires

Front

Rear

Coloring

87.0" (2,210 mm) 36.8" (935 mm) 46.1" (1,170 mm) 55.9" (1,420 mm) 10.8" (275 mm) 249 lbs. (113 kg) 3.2 gals. (12 l)

Telescopic forks Monocross suspension Drum

Drum 3.00 x 21 4.50 x 18 Sky Blue

Road Racing Machines TZ250

ENGINE Type

Displacement Bore and stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission

2-stroke, water cooled, twin 247 cc 54 x 54 mm 7.8:1 23.8 ft.-lbs (3.29kg-m)

@10,000 rpm (2) Mikuni VM34SS C.D.I. Push start

6-speed

Pre-mix (15:1)

2-stroke, water

66.4 x 54 mm

52.0 ft.-lbs

(7.2kg-m)

@9,500 rpm

(4) Mikuni

VM34SC

Push start

Pre-mix (15:1)

C.D.I.

6-speed

747 cc

7.3:1

CHASSIS

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Suspension

Front Rear Brakes

Rear

Front

Rear

Tires

Hydraulic disc (1) Front Hydraulic disc (1)

3.00 x 18 3.50 x 18 Clean White

76.2" (1,935 mm)

24.8" (630 mm)

37.4" (950 mm)

52.0" (1,320 mm)

6.7" (170 mm)

235 lbs. (106.5 kg)

6.2 gals. (23.5 f)

Telescopic forks

79.9" (2,030 mm)

25.1" (637 mm)

36.8" (935 mm)

54.7" (1,390 mm)

5.3" (135 mm)

342 lbs. (155 kg)

6.3 gals. (24 f)

Telescopic forks

4.00/5.75 x 18

Monocross suspension

Monocross suspension



ENGINE Type

Displacement Bore and stroke Compression ratio Maximum torque

Carburetion

Ignition Starting Lubrication Transmission

CHASSIS cooled, 4-cylinder

Overall length Overall width Overall height Wheelbase Ground clearance Dry weight Fuel tank capacity Suspension Front Rear

Brakes Front Rear Tires

Hydraulic discs (2) Hydraulic disc (1) Front 3.25 x 18

Coloring Clean White



Specifications subject to change without notice.

Rear

6620 ORANGETHORPE AVE. BUENA PARK. CALIF. 90620 LIT-11119-31-00 Printed in Japan 5