ROAD RIDING, MOTOCROSS STYLE! IS THERE ANY MORE EXCITING WAY TO START YOUR MOTORCYCLING?



Motocross. It's a young man's sport. All action, energy and excitement! Now some of that motocross feeling can be experienced by the road rider, courtesy of the new Yamaha DT125R..... a fully-equipped street machine but based closely on the Grand Prix motocross racer that took Dutchman, John van den Berk, to the 1987 World

125 cc Motocross Championship.
Let's stress right now, however, that you don't have to be a motocross racer, or even a motocross enthusiast, to enjoy the "instant response" power delivery and

quick manoeuvrability of the DT125R. In fact, you don't even need to be an experienced motorcyclist!

The 125cc class is a popular one with first-time riders in many countries

around Europe. And what better way to begin your motorcycling than with the


DT125R? Its aggressive "full race" styling is modified only slightly to

accommodate road-going equipment, plus technology and engineering match right up to the bike's eye-appeal. Long travel front forks and Monocross rear suspension provide a genuine "off-road" capability, so when the action gets slow on the streets, you can take to the trail! The sure handling and precision steering make the DT125R a superb performer on any terrain. Its engine is also up to any demands you want to make of it. Based on the World Championship-winning YZ125, with liquid-cooling, crankcase reed valve induction, YEIS and YPVS variable exhaust timing, it's one of the most advanced motors in its class. You can ride the DT125R

hard..... and keep riding it hard. Depend on it!



The DT125R instrument panel is neatly mounted behind a small head fairing. Panel contains speedometer, rev-counter and resettable trip meter.





The 230mm front brake disc is drilled to dissipate heat, while the 220mm rear disc uses the same caliper and master cylinder as our YZ motocross racers.

Monocross on the YZ G Box-section rising rate l absorber for movement.





TECHNICAL SPECIFICATIONS

Engine
Type Liquid-cooled, crankcase-reed
valve torque induction, 2-stroke
with YEIS and YPVS
Displacement 124 cc
Bore & stroke 56.4 x 50.0 mm
Compression ratio 6.8:1
Max. power 12.2 PS (9kW)/6500 rpm
Max. torque 1.4 kg.m/6000 rpm
Lubrication Autolube
Carburation VM26SS Mikuni
Ignition C.D.I.
Starter system Kick
Fuel tank capacity 10 L
Oil capacity 1.2 L
Transmission 6-speed
Final drive Chain
Chassis
Overall length 2160 mm
Overall width 830 mm
Overall height 1255 mm
Seat height 885 mm
Wheelbase 1415 mm
Min. ground clearance 315 mm
Dry weight 107 kg
Suspension Front Telescopic forks
Suspension Rear Monocross
Brakes Front Single Ø 230 mm disc
Brakes Rear Single Ø 220 mm disc
Tyres Front
Tyres Rear 4.10-18

Specifications and appearance of Yamaha motorcycles shown here may vary according to requirements and conditions and are subject to change without notice. For further details please consult your Yamaha dealer.

Always wear a helmet and eye protection.



Mitsui Machinery Sales (U.K.) Ltd. Oakcroft Road CHESSINGTON/SURREY KT9 1SA Tel: 01-3975111

Tlx: 929929

