




Years of Grand Prix success through engineering expertise have produced an alliance of safety with sporty efficiency.

That is the legacy of know-how impressed firmly on the FS1DX, Yamaha's 50-cc front runner,

a link between Sports Moped fun and economical easy riding. It is styled with flair, slim-line without being frail, surefooted and responsive with a front disc brake that is durable and reliable.







Engine and Gearbox

49-cc cast iron cylinder with deep finned alloy cylinder head, fitted with rotary disc valve with a bore of 40 mm and stroke of 39.7 mm. The well proven engine drives through helical primary gears to a 3-plate, 4-spring clutch.

Using a 4-speed gearbox the engine delivers top performance without sacrificing reliability or economy.

Autolube

Efficient engine lubrication is ensured by Yamaha's "Autolube" system.

Oil from a separate oil tank is injected into the induction port by a pump controlled by the throttle position and engine speed, monitoring oil supply to suit the load requirements of the engine.

Suspension

External spring hydraulic front forks with sporting rubber gaiters, working together with hydraulic rear shock absorbers, match top performance with competition developed roadholding.

Brakes

A 203 mm diameter disc brake at the front and a 110 mm diameter drum brake at the rear ensures safe braking under all conditions.

Accesories

The 6-Volt battery and tools are carried in the side cover. The seat incorporates a helmet lock for

Rear view mirror and indicators round off the sporting FS1DX.

SPECIFICATIONS

ENGINE

Tura 2 straka Pataru Valua Single
Type 2-stroke, Rotary Valve, Single
Displacement
Bore & Stroke
Compression ratio
Max. torque 0.52 kg-m @6,000 rpm
Lubrication systemAutolube
Starting system
Primary transmissionGear
Final transmission
Gearbox4-speed
Carburettor VM16SC
ClutchMulti plate, wet
Battery 6V, 4AH
Ignition type Magneto, CB/Coil
DIMENSIONS
Overall length
Overall width
Overall height
Seat height
Wheelbase
Weight (net)
Fuel tank capacity 6.5 lit.
Oil tank capacity 1.15 lit.

* Specifications subject to change without notice.

2.50-17-4PR



YAMAHA, It's a way of life



AMAHA MOTOR N. V.

Postbus 7829 PROF. E. M. Meverslaan 3 Amstelveen (Amsterdam), Holland ¹⁸⁸⁷ LIT-3MC-0107031-77BK/51.12×105 § Printed in Japan