

# Features: 500 XC cross country

New 488 cc, 6-speed engine. 40 mm Mikuni carburettor. Completely new designed frame, air filter box and fenders. New rear suspension system: Husqvarna ITC, offering additional progressivity, made by Öhlins. Travel 330 mm. New front hub with double leading brakes. New 18" rear wheel with Trelleborg tire. New Husqvarna handle bar. New designed front number plate and side panels.

# Features: 250 XC cross country

Modified engine and exhaust system. Motoplat magneto. Completely new designed frame, air filter box and fenders. New rear suspension system: Husqvarna ITC, offering additional progressivity, made by Öhlins. Travel 330 mm. New front hub with double leading brakes. New 18" rear wheel with Trelleborg tire. New Husqvarna handle bar. New designed front number plate and side panels.

# Features: 125 XC cross country

New modified cylinder, gearbox and exhaust system. Motoplat magneto. Completely new designed frame, air filter box and fenders. New 40 mm front fork. Travel 300 mm. New rear suspension system: Husqvarna ITC, offering additional-progressivity, made by Öhlins. Travel 330 mm. New front hub with double leading brakes. New 18" rear wheel with Trelleborg tire. New Husqvarna handle bar. New designed front number plate and side panels.





# **Technical Specifications**

Engine:

Single cylinder 2-stroke

	125XC	250XC	500XC
Displacement:	124 cc	245 cc	488 cc
Bore & Stroke:	55x52 mm	69.5x64.5mm	86x84 mm
Compression			
Ratio:	13.1:1	12.3:1	9.5:1

# Transmission:

6-speed gearbox Clutch:6-disc light alloy Chain:5/8"x1/4"

OTIGITI. 0/0 XT/T			
	125XC	250XC	500XC
Primary Transmission:	18:70	32:77	39:70
Overail Gear Ratios: 1st	37.3	23.1	19.1
2nd	27.0	16.7	13.3
3rd	20.6	12.7	10.0
4th	16.5	10.1	7.6
5th	13.9	8.6	6.4
6th	11.7	7.3	5.4
Secondary Transmission:	13:53	13:53	13:53

## Fuel:

Gas/oil mixture 1:25 (4%)
Tank Capacity: 125XC 10 lit (US gal.)
250/500XC 12 lit (US gal)

### Carburettor:

Mikuni 38 mm

# Electrical:

Motoplat CDI

## Frame:

Chrome moly tubing, heat treated.

#### Front Fork:

Husqvarna telescopic leading axle fork. Travel: 300 mm (11.8 in)

#### Rear Suspension:

Shocks: Husqvarna ITC, made by Öhlins Travel: 330 mm (13 in)

### Wheels & Brakes:

Tyres, front: 125XC Trelleborg 3.00x21"
250/500XC Trelleborg 3.00x21"Deep Grip
rear: 125XC Trelleborg 4.50x18"

250/500XC Trelleborg 4.50x18"Ten Master Trelleborg 5.00x18"Ten Master

Rims: Light alloy

Brakes: Ø 160 mm (6.3 in)

#### Dimensions:

Length:	2180 mm	(85.8 in)
Height:	1240 mm	(48.8 in)
Seat height:	1100 mm	(43.3 in)
Wheelbase:	1480 mm	(58.3 in)
Ground clearance:	300 mm	(11.2 in)
Weight: 125XC	96 kg	(211 lbs)
250XC	105 kg	(231 lbs)
600XC	109 kg	(240 lbs)

Specifications subject to change without notice.

