

# Husqvarna 175 WR/XC





## Features: 175 XC

The all new factory designed and assembled 175's are ready for any off road situation. The 175 XC excels at the higher speed, more suspension demanding courses of the eastern hare scrambles and the western desert races. Making this new 175 XC so suitable is the extra engine protection provided by the skid bars, the low maintenance rear brake system, the approved spark arrestor muffler and the capability of powering lights if they need to be added. Additional features are the efficient double leading shoe front brakes, waterproof airbox, Ohlins ITC shocks, vented front fender and the provision for installing a speedo drive to the front wheel. The 175 XC is ridden by Team Husqvarna Riders in the National Hare Scrambles series and anywhere a high speed, demanding course is met.



## Features: 175 WR

This National Enduro Class Winner is a serious competition motorcycle. The Enduro legal lighting is bright enough to get you home after dark and you can measure your distance to get there by the factory equipped speedometer set-up. Threading your way through wet, off camber rocks is made easy by the low seat height and the full width magneto that helps keep engine speeds steady. The WR is at home anywhere in the U.S. where you might find tight enduro trails mixed in with some rocks and elevation changes. Standard equipment on the WR includes nearly 10 inches of wheel travel, gas-filled Betor shocks, Trelleborg tires, high output ignition, spark arrestors and complete enduro set-up.



### Technical Specifications

	175 XC	175 WR
<b>Engine:</b>		
Displacement:	171 cc	171 cc
Bore x Stroke:	64.75 x 52	64.75 x 52
<b>Transmission:</b>		
Primary Ratio:	3.89:1	3.89:1
Overall Gear Ratios:	29.3:1 21.2:1 16.2:1 13.0:1 10.0:1 9.2:1	29.3:1 21.2:1 16.2:1 13.0:1 10.0:1 9.2:1
Clutch:	6 - disc light alloy	
Chain:	5/8" x 1/4"	
<b>Fuel:</b>		
Tank Capacity:	2.7 gallon	

<b>Carburetor:</b>	Mikuni 38mm	
<b>Electrical:</b>	175 XC Motoplat CDI	175 WR SEM CDI
<b>Frame:</b>	Chrome moly tubing Heat treated	
<b>Front Fork:</b>	Husqvarna telescoping leading axle 40mm stanchion 300mm (11.8") travel	
<b>Rear Suspension:</b>	Husqvarna designed ITC shock made by Ohlins 330mm (13") travel	Betor gas filled Twin shock 250mm (9.8") travel

<b>Wheels:</b>	21 in front, 18 in rear
<b>Tires:</b>	3.00 x 21 Trelleborg 4.50 x 18 Trelleborg
<b>Brakes:</b>	160mm (6.3") front & rear

	175 XC	175 WR
<b>Dimensions:</b>		
Length:	2180mm (85.8")	2190mm (86.2")
Height:	1240mm (48.8")	1250mm (49.2")
Seat Height:	980mm (38.5")	925mm (36.4")
Wheelbase:	1500mm (59.0")	1465mm (57.6")
Ground Clearance:	300mm (11.8")	300mm (11.8")
Weight:	211 lbs.	220 lbs.