


Kawasaki KH250





The sophisticated triple that's unique in the world.

You're looking at the only 3-cylinder 250 cc motorcycle in the world. There's nothing else like it in the class. Maybe that's one reason people who have the money to spend on much bigger, more powerful machines, still choose it. It's really different.

The 2-stroke 3-cylinder engine is a jewel. It likes to rev high and long and sounds like no other. There's plenty of

power for two-up touring and more than enough for tooling around town.




Disc brake, neat handling

The front disc brake makes arrow-straight stops with the rear drum. No dramatics. Safe. Sure. And this year the master cylinder has a sight gauge to check the oil level and a tamper-proof cap to it.

The handling is as neat as ever.

The geometry and suspension have always contributed to tidy riding on the KH250.

Another feature this year is the more comfortable 2-level seat like the ones fitted to larger Kawasaki road bikes. It's better for both rider and passenger and will be appreciated on longer weekend hauls in the country. In almost every other way Kawasaki's unique triple is unchanged.



Colours available: Candy Lime Green, Candy Cobalt Blue



KH250-B3 SPECIFICATIONS

ENGINE

Type	2-stroke, 3-cylinder, piston valve
Displacement	249 cc (15.19 cu. in.)
Bore and stroke	45.0 x 52.3 mm (1.77 x 2.06 in.)
Compression ratio	7.5:1
Ignition system	Battery and coil
Starting system	Kick
Lubrication	Superlube (oil injection)

TRANSMISSION

Type	5-speed, constant mesh, return shift
Shift pattern	1-N-2-3-4-5
Clutch	Wet, multi-disc

FRAME

Type	Tubular, double cradle
Suspension: Front/Rear	Telescopic fork/Swing arm
Tyre size: Front/Rear	3.25-S18 4PR/3.50-S18 4PR

BRAKES

Front	Single disc brake, effective disc dia. 226 mm (8.9 in.)
Rear	Drum, 180 x 30 mm (7.09 x 1.18 in.)
Braking distance	12 m @ 50 kph (39 ft @ 31 mph)

DIMENSIONS

Length, overall	2,085 mm (82.1 in.)
Width, overall	760 mm (29.9 in.)
Height, overall	1,045 mm (41.1 in.)
Wheelbase	1,375 mm (54.1 in.)
Ground clearance	155 mm (6.1 in.)
Dry weight	160 kg (353 lbs.)
Fuel tank capacity	14 litres (3.08 Imp. gal.)

The specifications mentioned here apply to and have been achieved by production models under standard operating conditions. We intend only to give a fair description of the motorcycles and their performance capabilities but these specifications may not apply to every machine supplied for sale. Kawasaki Heavy Industries, Ltd. reserves the right to alter specifications without prior notice.

THE KAWASAKI CENTRE
WELCH & CO. LTD.
AVON ST.
BRISTOL, BS20 0PZ Tel. 778866

Kawasaki
ENGINE AND MOTORCYCLE GROUP

Wear a helmet. Enjoy safe riding.

99980-013-13 Printed in Japan