

TT 500





The TT500 is a perfect mix of traditional engineering and modern racing technology. The result is a new concept in off-road competition motorcycles; a machine that is sure to make its mark in Enduro, scrambles and TT competition.


The classic overhead cam, four-stroke

single delivers smooth torque even at low rpm's. And the five-speed transmission distributes power over a broad range. Mount that in a modern, lightweight motocross frame. Add heavy-duty, long travel front forks, forward-mounted nitrogen/fluid rear shocks and heavy-duty wheels. What you have is a


motorcycle with the same handling and control as Yamaha's world championship motocrossers.

The TT500. With its versatile big bore performance and exceptional handling combines the best of both worlds.


Features




Overhead cam, four-stroke single, develops smooth power over a broad range. Typical of big bore singles, there is quick response and abundant torque even at low rpm's.




Wide-ratio five-speed transmission has a short-throw lever for fast, positive shifts. The wide-ratio gear cluster allows the versatility of power and speed for a wide variety of racing conditions.



Single-downtube cradle frame is light but strong. The low profile creates a low center of gravity for better balance and positive handling.



Long travel, heavy-duty front forks soak up sharp jolts without bottoming. Heavy-duty wheels front and rear equip the TT500 for comfort, control and durability over the roughest terrain.



Forward-mounted nitrogen/fluid shocks provide greater rear wheel travel for better control, consistent traction and superior fade-resistant damping.



**TT500C
ENGINE**

Type..... 4-stroke single
 Displacement 499 cc
 Bore and Stroke 87×84 mm
 Compression ratio 9.0 : 1
 Maximum torque 27.8 ft.-lbs. @5,500 rpm
 Carburetion (1) Mikuni 38 mm
 Ignition Magneto
 Starting Kick
 Lubrication Dry sump
 Transmission 5-spd.

CHASSIS

Overall length 83.1"
 Overall width 36.8"
 Overall height 44.1"
 Wheelbase 55.9"
 Minimum ground clearance 8.5"
 Dry weight 262 lbs.
 Fuel tank capacity 2.2 gal.
 Oil capacity 2.3 qts.
 Suspension
 Front Telescopic fork
 Rear Swing arm
 Brakes
 Front Drum
 Rear Drum
 Tires
 Front 3.00×21
 Rear 4.60×18

** Specifications subject to change without notice.*

**Someday,
you'll own a Yamaha.**

YAMAHA INTERNATIONAL CORPORATION
 6600 Orangethorpe Ave., Buena Park, California 90620
 Printed in Japan LIT-11036-20-00

