



XR200R





XR200R

MODEL: 1982 XR200R-C

TYPE: Enduro

COLOURS: Red only

AVAILABLE: April 1982

KEY FEATURES

- Big bore, overhead cam, four-stroke, single-cylinder engine.
- Pro-Link™ rear suspension system with four-way adjustable rebound damping and remote aluminium body reservoir provides 246mm of wheel travel.
- Large 35mm diameter air-assisted lead axle front forks with dual low friction Syntallic™ bushings and 250mm of travel.
- Large tapered roller steering head bearings.
- Box section rear swing arm pivots on needle bearings.
- Quick release front and rear wheels.
- Tubular frame provides 340mm of ground clearance.
- 90° side pull type throttle.
- Tool bag with a single multi-purpose tool.
- Flexible odometer reset knob resists damage.
- Lightweight injection-moulded plastic fuel tank with large filler neck.

- High-performance capacitor discharge ignition (CDI) eliminates maintenance.
- Kick starter actuated compression release for easy starting.
- Six-speed close ratio transmission.
- Large plastic front and rear fenders provide excellent mud protection.
- Unique dog-leg style reverse ball control levers help prevent brush snagging.

NEW FEATURES

- New rear shock assembly with works-style damping and lighter remote reservoir.
- Improved front fork spring and damping rates.
- New lighter and stronger front/rear rims.
- New design tyres for improved traction.
- New design rim locks.
- New chain guide uses slider for longer wear.

SPECIFICATIONS

Engine	195cc OHC four-stroke single
Bore and Stroke	65.5 mm x 57.8 mm
Compression Ratio	10:1
Carburettor	26 mm piston valve
Ignition	Capacitor discharge
Starter	Kick starter, with automatic compression release
Transmission	Six-speed
Final Drive	Chain
Length	2,080mm
Width	815mm
Height	1,209mm

Wheelbase	1,355mm
Seat Height	890mm
Ground Clearance	340mm
Fuel Capacity	2.1 gallons, including 0.5 gallon reserve
Wheels	Spoked
Tyres: Front	3.00-21 enduro-knobby
Rear	4.10-18 enduro-knobby
Suspension: Front	Air-assist leading axle forks, 250mm travel
Rear	Pro-Link™ with adjustable clamping and remote reservoir, 246mm travel
Brakes: Front	Drum
Rear	Drum
Dry Weight	101kg