



XT500

- O Classic single cylinder power unit
- Chain driven single overhead camshaft Braced handlebars
- O Large flywheel magneto for low speed torque
- 5-speed gearbox
- Lightweight cycle parts
- O Long travel front suspension
- O Steeply angled, adjustable rear suspension
- Gold anodised alloy wheel rims
- O High level exhaust system

- O Crankcase shield
- O Contoured levers fitted with rubber shrouds
- O Deeply padded seat
- Oil carrying frame
- Exhaust valve lifter for easy starting
- O Quick action throttle
- O Rubber mounted indicators
- Tachometer

ENGINE

Type Cylinder Displacement Bore & Stroke Compression Ratio Maximum Horsepower Maximum Torque Lubrication System Starting Ignition Type Transmission

4 stroke OHC Single 499cc 87.0×84.0mm 9.0:1 32hp 6500rpm 4.0kg-m 5500rpm Dry sump. Primary kick Magneto CB/Coil 5 speed

DIMENSIONS

Overall Length Overall Width Overall Height Wheelbase Ground Clearance Seat Height Weight Fuel Tank Capacity Oil Capacity Tyres-Front Rear Brakes-Front

Rear

2175mm 875mm 1170mm 1420mm 220mm 855mm 140kg 8.5 litres 2.4 litres 3.25–21–4PR 4.00–18–4PR

Drum Drum