

## THE YAMAHA YB100—SIMPLE AND STRAIGHTFORWARD.

Hidden beneath the smart, modern appearance of the Yamaha YB100 is an old-fashioned virtue . . . simplicity. Everything about this neat little utility lightweight has been made easy to operate, easy to handle and easy to maintain.

Not that the YB100 lacks many of the technical innovations made famous by Yamaha over the years. Zippy performance via rotary valve induction and precise automatic oiling are both featured on the basically simple, 97cc two-stroke, single cylinder engine.

Designed very much with the short-journey commuter in mind, the YB100 has deep mudguards to ward off road splashes, a chain guard to keep lubricant off the rider's clothes and rocker-pedal gearchanging to keep the shine on his shoes.

Comfort, cleanliness and crisp performance, all in a single economical package . . . the Yamaha YB100.

as smoothing out the bumps in the roads. Drive chain is covered by a large chain Comfortable dual seat has a low height of guard to keep lubricant splashes off the only 785mm to enable the commuter to rider's clothing. Another 'plus' for the get both feet firmly on the ground at traffic commuter. lights and other stops. 'Labyrinth-seal' drum brakes at front and rear keep out both dust and water. maintaining their efficiency under any weather conditions. Efficient No messy pre-mixing of oil and petrol with rotary-valve the YB100. Yamaha's 'Autolube' system induction gives the does the job via a special pump linked to YB100 a smooth spread

switch.

Simple, easy-to-read instrument console

indicator lamps for gearbox neutral, high

beam and turn signal, plus main ignition

includes all essentials for riding: speedometer, odometer, oil warning lamp,

## YB100 SPECIFICATIONS

ENGINE	
Type	2-stroke, rotary valve, single
Displacement	97 сс
Bore and stroke	$52.0 \times 45.6 \text{ mm}$
Compression ratio	6.5:1
Max. power (DIN)	9.8 PS (7.2 kW) @8,000 rpm
Max. torque (DIN)	0.89 kg-m (8.7 Nm) @5,500 rpm
Lubrication	Autolube
Carburation	Mikuni VM20SC
Ignition	Flywheel magneto
Starter system	Kick
	8.6 <i>l</i>
Oil tank capacity	1.2 <i>l</i>
Transmission	4-speed
Final transmission	Chain drive

## CHASSIS 1,850 mm Overall length 1,850 mm Overall width 735 mm Overall height 1,035 mm Seat height 785 mm Wheelbase 1,180 mm Min. ground clearance 140 mm Dry weight 84 kg Suspension Front Telescopic forks Rear Swing arm Brakes Front Drum Rear Drum Tyres Front 2.50-18

The four-speed transmission features a'

'rocker' type shift pedal. All gearchanging

can be done with the sole of the foot or the

heel, thus protecting the rider's footwear.

Mitsui Machinery Sales (U.K.) Ltd. Oakcroft Road CHESSINGTON/SURREY KT9 1SA Tel: 01-3975111

Tel: 01-3975111 Tlx: 929929

the throttle, delivering exactly the right

amount of oil at any throttle opening. Oil

level in the 1.2-litre tank can be checked at

a glance through the built-in sight glass.



of bower across the rpm range. Good low-down torque is an

aid to inner-city commuting, while the 97cc two-stroke single

can still cruise respectably at highway speeds. Large-capacity

air filter and exhaust silencer keep noise levels way down.

Telescopic front forks and swinging arm

confidence-inspiring roadholding as well

rear suspension are both hydraulically

damped. This combination gives